



Mustang P-51 High Speed Opener In 3 Sizes
Lowest operating cost

Greatest flexibility, surgical placement of plant nutrients.
Triplex Injection with the lowest level of soil disturbance.



Mustang Openers are High Speed with low soil disturbance and low horsepower.

The openers can be arranged in multiple ranks or can be closely mounted side by side.
The slim design allows an unobstructed flow or residue with a maximum overall width of 8 inches...the narrowest opener design for nutrient application.
The Injector Foot is not a shank or knife. The Injector Foot holds the injector into place with streaming liquid flow into the narrow slot.
A diluted vertical band is created with liquids including NH3.
The unit seals off at the 2 inch depth as the foot makes it's pass.
The root targeted, positional band is unique. A 3 to 4 inch vertical root interception of TAPPS and TAPPKTS is implemented with the Triplex Injection.
P-51, banding depth 4 inch, 4 bolt hub, 1,500 pound grease seal lube hub, 3/8 x 20 double edged blade. 145 pounds, Max 500 pounds down pressure to 10 mph.

Yielder Category.

P-51B, banding depth 5 inch, 5 bolt, Cat Duo Cone Floating Ring Seals, Oil Running, 3,300 pound Hub, 3/8 x 22 inch blade. 185 pounds. Max 650 pounds down pressure to 15 mph.
P-51C, banding depth 6 inch, 5 bolt, Cat Duo Cone Floating Ring Seals, 3,300 pound, Oil Running Hub, 3/8 x 24 inch. 225 pounds. Maximum 650 pounds down pressure to 15 mph.
P-51 B and C are designed for Yielder 5 bolt hubs.
New or used Yielder blades can be used.
Yielder blades are typically 1/4 x 24" seeding or, 5/16 or 3/8 x 24" as deep band blades.
Yielder blades at 21 to 20 inch are still usable on the P-51 series openers.



Flexibility.

Mounts to air-seeder frames. Yielder Drills can be modified to lower deep banding costs.
Can be mounted to Deere 1890 as a banding unit.
The Deere 2510 can be improved by mounting Mustang openers at the back of the tool bar making a 15 inch tool bar.
The Bourgault 8825 can be set up with a second set of tooling for low soil disturbance application of wheat.
Can be inter-mounted on Bourgault 3310 replacing the Bourgault fixed angle opener allowing banding with virtually no soil disturbance.
The Mustang Opener can be mounted on planters and are highly reliable.
High Speed Tool Bars can be designed to widths of 120 feet with lower cost and more options to change spacing to match the crops raised.
Allows side dressing treatments of winter wheat down to 10 inch spacing with RTK guidance.

Triplex Injection.

Applies 3 different products formulating TAPPS, TAPPKTS, TAPPKTS plus organic products, TAPPKTS plus HCl.
New bio systems... banding into growing roots.
Ideal for banding directly into wheat.
Virtually no root damage when side dressing seedling corn to a 6 inch depth with the P-51C.
Allows very deep placement of phosphate at 6 inch depth in moist soil conditions with the P-51C.

P-51D
Fumigant Injection
28" diameter available

Widely Tested, the Mustang seals the slot in all tested soil conditions in 8 states.

Allows low cost banding on 10 inch centers to 15 inch centers.
Low soil disturbance...with a soil saving warranty.
Lowest operating cost.... lowest known operating cost with the P-51B and C at banding depths to 6 inch in moist soil conditions.
A 3 year development history across North America. Released for export in three different arrangements.

4501 East Trent Avenue
Spokane, Washington 99212
509-535-9925

www.exactrix.com

